

Teak Protector Classic

Technical Data Sheet

Applications:

Teak Protector Classic is a coloured and high-quality protective agent for teak. It is based on the latest technology. It prevents soiling, drastically reducing the growth of algae.

It also impregnates the wood, which makes it more durable and prevents deterioration. The top layer is also water and grease-repellent. The surface does not become shiny, and the product gives the classic light-brown colour. Ideal for maintaining new and restoring the colour of greyed teak. Does not affect sealant and does not make the teak deck slippery.

Instructions for use:

1. Protect surfaces that cannot be treated.
2. Ensure sufficient ventilation.
3. Always shake the bottle well before use.
4. The surface to be treated must be completely clean and dry.
5. Apply the Teak Protector Classic with a brush or a cloth. Allow the product to soak in for a few minutes.
6. Thoroughly rub it out using a clean and dry cloth to remove excess product.
7. Repeat the treatment where necessary.

Product usage:

This depends entirely on the porosity and humidity level of the surface to be treated and the selected application method.

Depending on the surface porosity, coverage can vary between approximately 5 m² per litre for porous surfaces, to up to 15 m² per litre for slightly porous surfaces.

The above usage is indicative and should be determined by first applying to a small test area.

Considerations during application:

Always place a reference test on the to be treated surfaces in order to determine both adhesion and the technical and aesthetic result.

Specifications:

Appearance:	Liquid
Color:	Brown
Scent:	Characteristic
Flash Point:	27 °C
Density:	0,88 g/cm ³

Hazard symbols and H & P statements (CLP):



GHS02
Danger

GHS07

H-Phrases: H225 - Highly flammable liquid and vapour.

H336 - May cause drowsiness or dizziness.

P-Phrases: P210 - Keep away from hot surfaces, open flames, sparks, heat.
No smoking.

P233 - Keep container tightly closed.

P312 - Call a doctor, a POISON CENTER if you feel unwell.

P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

Packaging and industrial waste:

Treat as industrial waste in accordance with the applicable regulations. Collect process water in accordance with the applicable local regulations.

This information is based on laboratory tests and practical experience.

For application and use, please adhere strictly to the descriptions in the technical product information sheets and MSDS sheets. We do not accept any liability for any advice provided by us. The application, use and handling of the products are the sole responsibility of the user. All our documents and texts have been prepared to the best of our knowledge, language and translation errors are expressly excluded and can never lead to any liability.

Teak Protector Classic is part of the Impressed Pro[®] Marine product range, developed to clean and preserve all types of all common surfaces and materials on and around boats and/or ships. For specific questions and applications, as well as for the up-to-date TDS and MSDS sheets, please visit our website www.impressedpro.com or contact your distributor and / or technical advisor.