

Gelcoat Speed Protector

Technical Data Sheet

Applications:

Gelcoat Speed Protector is a high-quality protective agent based on the most innovative technologies. Protects the gelcoat and provides extra shine and protection after washing.

It also prevents the adhesion of dirt. Safe for polyester, plastic, painted and metal surfaces, including chrome, stainless steel and aluminium. Gelcoat Speed Protector is also excellent as part of standard gelcoat maintenance as well as for maintaining surfaces already treated with a Marine Coat.

Instructions for use:

1. Dilute Gelcoat Speed Protector with clean water in a ratio of 1:100 to a maximum of 1:200.
2. First clean the surface with Hull Cleaner or a similar product.
3. Then apply Gelcoat Speed Protector evenly to the surface using a pulveriser/pressure sprayer or, if necessary, a sponge.
4. Gelcoat Speed Protector may be applied to wet surfaces.
5. Always rinse the surface thoroughly with clean (cold) water.

Product usage:

Depending on the porosity of the surface, approximately 40 to 80 washing operations per litre.

The above usage is indicative and should be determined by first applying to a small test area.

Considerations during application:

Always place a reference test on the to be treated surfaces in order to determine both adhesion and the technical and aesthetic result.

Specifications:

Appearance:	Liquid
Color:	Dark pink, red.
Reuk:	Fruity
pH:	7
Solubility:	Completely soluble in water.

Hazard symbols and H & P statements (CLP):



GHS07
Warning

H-Phrases: H315 - Causes skin irritation.

H319 - Causes serious eye irritation.

P-Phrases: P264 - Wash hands thoroughly after handling.

P280 - Wear protective gloves, eye protection.

P302+P352 - IF ON SKIN: Wash with plenty of soap and water.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P332+P313 - If skin irritation occurs: Get medical advice/attention.

P337+P313 - If eye irritation persists: Get medical advice/attention.

Packaging and industrial waste:

Treat as industrial waste in accordance with the applicable regulations. Collect process water in accordance with the applicable local regulations.

This information is based on laboratory tests and practical experience. **For application and use, please adhere strictly to the descriptions in the technical product information sheets and MSDS sheets.** We do not accept any liability for any advice provided by us. The application, use and handling of the products are the sole responsibility of the user. All our documents and texts have been prepared to the best of our knowledge, language and translation errors are expressly excluded and can never lead to any liability.

Gelcoat Speed Protector is part of the Impressed Pro[®] Marine product range, developed to clean and preserve all types of all common surfaces and materials on and around boats and/or ships. For specific questions and applications, as well as for the up-to-date TDS and MSDS sheets, please visit our website www.impressedpro.com or contact your distributor and / or technical advisor.

Produced and developed:

Cleaning Care Products International B.V.
Noord 49 L-M, 2931 SJ Krimpen aan de Lek - The Netherlands
www.ccp.nl - info@ccpi.nl

Exclusive distributor:

Graafship Maintenance WorldWide B.V.
Spinel 50, 3316 LG Dordrecht - The Netherlands
www.impressedpro.com - info@impressedpro.com